

2008

Substratum Assessment of Various Minimum Torsional Design Philosophies via Structural Optimization Techniques

Bakas, Nikolaos

WCCM

<http://hdl.handle.net/11728/6599>

Downloaded from HEPHAESTUS Repository, Neapolis University institutional repository

SUBSTRATUM ASSESMENT OF VARIOUS MINIMUM TORSIONAL DESIGN PHILOSOPHIES VIA STRUCTURAL OPTIMIZATION TECHNIQUES

* Nikos P. Bakas¹, Nikos D. Lagaros² and Manolis Papadrakakis³

¹ National Technical
University of Athens
Athens, GR-15780, Greece
nibas@central.ntua.gr

² National Technical
University of Athens
Athens, GR-15780, Greece
nlagaros@central.ntua.gr

³ National Technical
University of Athens
Athens, GR-15780, Greece
mpapadra@central.ntua.gr

Key Words: *Torsion, Centre of Strength, Ductility Demands, Overstrength, Nonlinear Time history.*

ABSTRACT

A number of articles have been published, studying the issue of torsional response of reinforced concrete (RC) buildings [1], the majority of them were focused on the strength of the structural elements or the structure as a whole. In the work by Kan and Chopra [2] the Base Shear Torque (BST) surfaces have been proposed which provide a measure of the structural system's strength reduction due to the torsion inflicted by earthquake loading. On the other hand, some other researchers examine the additional displacements caused on the structural system due to the torsional response. Paulay [3] suggested maximizing the ductility capacity in an effort to undertake the increased displacement due to the torsional response.

Although a structural system can be assessed based on the above mentioned criteria, where the designer lacks the necessary design procedure to accomplish them. This can be achieved in a robust and reliable way through a structural optimization procedure [4]. In this work an automated topology based optimization procedure is proposed, in order to assess the two above mentioned, most widely accepted design philosophies. According to a performance-based framework, every candidate optimum designs encountered during the optimization procedure is assessed via nonlinear time history analyses. Through the optimization procedure it can be seen whether the maximum ductility or the maximum strength criterion leads to the best design. The two optimum designs are compared by performing life cycle cost analysis.

REFERENCES

- [1] C. L. Kan and A. K. Chopra, Linear and nonlinear earthquake response of simple torsionally coupled systems, *Report No. EERC 79 J03, Earthquake Engineering Research Center, University of California, Berkeley, CA, 1979.*
- [2] Juan C. De La Llera and Anil K. Chopra, Understanding the inelastic seismic behaviour of asymmetric-plan buildings, *Earthquake Engineering and Structural Dynamics*, vol. 24, 549-572 (1995)

- [3] T. Paulay, Torsional mechanisms in ductile building systems, *Earthquake Engineering and Structural Dynamics*, 27, 1101-1121 (1998)
- [4] Lagaros, N.D., Papadrakakis, M., Bakas, N., Earthquake resistant optimum design of 3D reinforced concrete structures, *J. Earth. Engrg.*, 533-565 Vol. 10, No. 4, 2006.